

Rigid Core Collection — Product Specifications

RIGID CORE 402 · 605 · 610 · 810 · Planet Tiles — 100% waterproof rigid core vinyl flooring

SERIES	PLANK / TILE SIZE	TOTAL THICKNESS	WEAR LAYER	ATTACHED BACKING	INSTALLATION
RIGID CORE 402	7.17" × 48"	5mm (4mm + 1mm IXPE)	12 mil	1mm IXPE	Floating click-lock
RIGID CORE 605	7.17" × 48"	6mm (5mm + 1mm IXPE)	22 mil	1mm IXPE	Floating click-lock
RIGID CORE 610	9" × 60"	6.5mm (5.5mm + 1mm IXPE)	22 mil	1mm Klein Blue IXPE	Floating click-lock
RIGID CORE 810	9" × 62.6"	8mm (6.5mm + 1.5mm IXPE)	30 mil	1.5mm Klein Blue IXPE	Floating click-lock
Planet Tiles	12" × 24"	6mm	12 mil	—	Floating click-lock

- 100% Waterproof
- 3D Printed Décor
- Radiant Heating Compatible (≤85°F)
- Install Over Most Hard Floors
- Perfect Match Trims Available
- Residential & Commercial Warranty

Installation and use temperature range 55–95°F (13–35°C). Maintain 1/4" expansion gap at all walls and fixed objects. RIGID CORE 605, 610 and 810 include pre-attached IXPE backing — do not add additional underlayment. Specifications subject to change; confirm current specifications with your Benchwick representative before ordering.