

SUPEROAK Collection — Product Specifications

Hybrid wood planks — real wood veneer, non-PVC core, MattMaster electron-beam coating

SERIES	FORMAT	PLANK / PANEL SIZE	TOTAL THICKNESS	HIGHLIGHTS
SUPEROAK Lite	Hybrid wood plank	7.7" × 47.78"	9.5mm	Accessible entry to hybrid wood
SUPEROAK Select	Hybrid wood plank	7.5" × 48"	12mm	0.6mm true wood veneer
SUPEROAK Elite	Hybrid wood plank	9" × 60"	10mm	Wide-plank format, enhanced wear layer
SUPEROAK Plus	Hybrid wood plank	9.8" × 72.7"	12mm	Wide, long format
SUPEROAK Acoustic Wall	Acoustic wall panel	114.17" × 23.62"	0.82" (21mm)	NRC 0.7+, polyester fiber backing

- Real Wood Veneer
- Non-PVC Construction
- AC5 Commercial Rating
- 100% Waterproof
- MattMaster EB Coating
- 30 Unique Patterns Per Box
- Radiant Heating Compatible (≤85°F)

Acclimate planks 48–72 hours at 60–80°F and 35–65% relative humidity before installation. Over concrete subfloors, install a 6-mil polyethylene vapor barrier with seams overlapped 8" and taped. Specifications subject to change; confirm current specifications with your Benchwick representative before ordering.